TECHNICAL DATA SHEET PLASTICS

issued: August 1, 2016



Finalux G-748



Dispersant, Lubricant (Pentaerythritol Tetrastearate)

CAS No. 115-83-3

EINECS # 204-110-1

PHYSICAL PROPERTIES **PHYSICAL PROPERTIES FASTNESS PROPERTIES**

Solubility in Water Density g/cm³ Melting Point 63°C +/-5 / 145°F +/-9

Flash Point 343°C / 650°F Acid Value 8.0 Maximum

Iodine Value 1.0 Maximum

Insoluble Warpage Bio Based Content Vegetable

PARTICLE SIZE Powder 100-120µm

APPLICATION PROFILE

Film	Wire & Cable	Injection Mold	Fiber	Com- pounding	Blow Molding	Roto Molding	Sheet Extrusion	Pipe Extrusion
6	6			6	6		۵	۵

LEGEND

recommended

♦ partially recommended

REGULATORY

FDA	GRAS	Mercosur 23/04	EU 10/2011	ASTM 963	EN 71/III	Mercosur 108/2005 & 369/2007	RoHS II	SVHC Compilant	Propo- sition 65
		۵				۵	۵	۵	۵

RESIN TYPE

ABS	ASA	CA/CP/ CAB	EVA	IONOMER	PA	PC	PE	PP	PS	PBT	PES
۵	۵	\Diamond	\Diamond	\Diamond	۵	۵	\Diamond	\Diamond	\Diamond	۵	۵
PET	POM	PPO	PUR	PVC	PMMA	SAN					
	A	A	A	A	A						

Disclaimer:

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we assume no obligation, express or implied, or liability for the use obligation, express or implied, or liability for the use of or reliance on the information and data provided. The information is furnished upon condition that the person receiving it shall make their own determination of the suitability of the material for their particular purpose.

GLENDALE HEIGHTS, IL 60139